SwirlFlo® Single Wall Mount Fountain Vandal Resistant Non-Filtered Non-Refrigerated Stainless

Model EDFPBMV114K

PRODUCT SPECIFICATIONS

SwirlFlo® Single Wall Mount Fountain Vandal Resistant Non-Filtered Non-Refrigerated Stainless. Furnished with Vandal Resistant bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 1 station(s).

Finish:	Stainless Steel
Power:	No Electrical Required
Bubbler Style:	Vandal Resistant
Activation by:	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Capacity:	Non-refrigerated
Dimensions (L x W x H):	14" x 18-3/8" x 11-5/16"
Approx. Shipping Weight:	23 lbs.
Installation Location:	Indoor
No. of Stations Served:	1

 Mechanically-Activated unit continues to supply water in event of service disruptions.



Included with Product:

Fountain with Back Plate, Surface Mounting

▼ Ships in multiple boxes.

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 NSF/ANSI 61 (Q≤1) & 372 (lead free) NSF REG4







Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 97921C

Water Systems are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty. Warranty (PDF)

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



SwirlFlo® Single Wall Mount Fountain Vandal Resistant Non-Filtered

on-Ref	rigerate	ed Stai	nless
Mod	el EDF	PBMV	114K

Optional Accessories				
<u>EWF172</u>	Universal Filtration Kit (1500-Gallon) Spec Sheet (PDF)			
AP99	Access Panel 9" x 9" x 6" Spec Sheet (PDF)	18000		
<u>98481C</u>	Bubbler Kit Water-Efficient Vandal-Resistant Spec Sheet (PDF)	2		

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.


SwirlFlo® Single Wall Mount Fountain Vandal Resistant Non-Filtered Non-Refrigerated Stainless


Model EDFPBMV114K


INSTALLER NOTE

This drinking fountain is furnished with a bubbler and valve including all connecting fittings which are manufactured of completely lead free material. Shut off valve (not furnished) to accept 3/8" O.D. unplated copper tube.

OPERATION OF QUICK CONNECT FITTINGS








WARNING: The free-resistant box must be installed on an interior heated wall where the temperature does not drop below 50° F (10° C). The front of the box must have unobstructed air flow. Failure to maintain the interior wall temperature and the inside of the freeze resistant box above 50° F (10° C) can result in damage to the box which could result in unrestricted

WALL LAYOUT

FRONT & SIDE VIEW



LEGEND

A = 7/8" (22mm) Ø Hole for water supply tube
B = 1-3/4" (44mm) Ø Hole for waste line
C = 3/8" (10mm) Ø Slots for mounting hanger bracket to wall

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.