Halsey Taylor® OVL-II™ Bi-Level Fountain Non-Filtered Non-Refrigerated Stainless Model OVL-II SEBP

PRODUCT SPECIFICATIONS

Halsey Taylor® OVL-II™ Bi-Level Fountain Non-Filtered Non-Refrigerated Stainless. Furnished with Double Bubbler ™. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 2 station(s).

Order ID:	7434004883
Finish:	Stainless Steel (S)
Power:	No Electrical Required
Bubbler Style:	Double Bubbler ™
Activation by:	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Capacity:	Non-refrigerated
Dimensions (L x W x H):	38-1/4" x 18-5/8" x 20-1/8"
Approx. Shipping Weight:	55 lbs.
Installation Location:	Indoor + Outdoor
No. of Stations Served:	2

**When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Exclusive Double Bubbler which projects two separate streams that converge to form a fuller, more satisfying drink.

Included with Product: Fountain Ships in one box.

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 NSF/ANSI 61 (Q≤1) & 372 (lead free)





Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 97638C

Water Systems are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, reserves the right to change product specifications without notice. Please visit for the most current version of product specification sheets. This specification describes product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



Halsey Taylor® OVL-II™ Bi-Level Fountain Non-Filtered Non-Refrigerated Stainless Model OVL-II SEBP

		
Optional Accesso	ries	
<u>HWF172</u>	Halsey Taylor WaterSentry® VII Filter Kit (Coolers + Fountains) Spec Sheet (PDF)	
MPW200	In-wall Mounting Plate for Bi-level On-wall Non-refrigerated Fountains Spec Sheet (PDF)	
HTOVLAPR	Halsey Taylor® Cane Apron for OVL-II™ Models (Gray) <u>Spec Sheet (PDF)</u>	
ACCESS12X38-5	Stainless Steel Access Panel for Bi-Level Architectural Fountains Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, reserves the right to change product specifications without notice. Please visit for the most current version of product specification sheets. This specification describes product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

18"

457mm MOUNTING INSTRUCTIONS 5/8" 13-5/16" Refer to diagrams for rough-in of plumbing. 16mm 2-5/16" 338mm Mount wall plate assembly to wall per the 59mm installation instructions. Hang fountain panel over the wall plate assembly. Attach fountains to wall plate assembly. Water service line and waste line are to be assembled as required. Final check for leaks and correct functions of fountain should be made. (For details see the installation instructions.) Installation requires trap to be installed in wall. A service supply stop must be 18-3/8" 178mm installed at the fountain inlet line. Trap and 467mm service stop not included. CAUTION –Fountain must be securely 78_{mm} bolted to wall. For wall support required locations see installation instructions provided with panel and fountains. 9-7/8" 33" OPERATING PRESSURE 868mm 251mm Supply Water - 105 psi maximum 686mm ADA WALL LINE REQUIREMENTS 2" X 3" SLOT FOR A & B (2) 18-3/4" 476mm "B' 2-3/4" 70mm "A" WALL PLATE ASSEMBLY | 4 | 4 体 4 BACK PANEL 25mm 6" 1/2' 1/2" Ø 3/8" (20) 1.10mm 152mm 13mm 13mm 1 -**\$**-1/2" 25mm 6" 13mm 152mm 5-1/4" 5-1/4" 43-5/8" 34-5/8" |133mm 5-1/4" 5-1/4" 133mm 1108mm 879mm 133mm 133mm 8" 28-1/2" 203mm 203mm 203mm 16" 203mm 724mm 31-7/8" *- STUDS REQUIRED 810mm FOR FRAMED WALL 406mm 406mm 25-3/4' CONSTRUCTION 654mm 5-1/4" 133mm LEGEND:

A = 1-1/4" O.D. Waste Tube (Trap And Elbow Not Provided) B = 3/8" O.D. Unplated Copper Tube Connect (Water Inlet) C = 1/4" DIA. (6mm) Holes For Mounting Plate To Wall

In keeping with our policy of continuing product improvement, reserves the right to change product specifications without notice. Please visit for the most current version of product specification sheets. This specification describes product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.