

PRODUCT SPECIFICATIONS

SwirlFlo® Bi-Level Fountain Non-Filtered Non-Refrigerated Freeze Resistant Stainless. Features shall include Freeze Resistant. Furnished with Flexi-Guard® Safety Bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 2 station(s).

Special Features:	Freeze Resistant
Finish:	Stainless Steel
Power:	No Electrical Required
Bubbler Style:	Flexi-Guard® Safety Bubbler
Activation by:	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Capacity:	Non-refrigerated
Dimensions (L x W x H):	38-1/2" x 19" x 21-15/16"
Approx. Shipping Weight:	82 lbs.
Installation Location:	Indoor + Outdoor
No. of Stations Served:	2

****When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.**

Special Note: Requires In-Wall Carrier MPW200 (sold separately)

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Freeze Resistant:
 - Depending on specific installation, freeze resistant system is located either below frost line or in temperature controlled space.



Included with Product: Fountain with Back Plate, Freeze Resistant Box

▼ Ships in multiple boxes.

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

Buy American Act

NSF/ANSI 61 (Q≤1) & 372 (lead free)



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

[Installation Instructions \(PDF\) - 98010C](#)

[Installation Instructions \(PDF\) - 97566C](#)

Water Systems are warranted for 12 months from date of installation.

Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

[Warranty \(PDF\)](#)

PART: _____ QTY: _____

PROJECT: _____





CONTACT: _____

DATE: _____

NOTES: _____

APPROVAL: _____

In keeping with our policy of continuing product improvement, reserves the right to change product specifications without notice. Please visit [www.elkay.com](#) for the most current version of product specification sheets. This specification describes product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Optional Accessories		
EWF172	Universal Filtration Kit (1500-Gallon) Spec Sheet (PDF)	
MPW200	In-wall Mounting Plate for Bi-level On-wall Non-refrigerated Fountains Spec Sheet (PDF)	
ACCESS12X38-5	Stainless Steel Access Panel for Bi-Level Architectural Fountains Spec Sheet (PDF)	
LKAPR1	Cane Apron for SwirlFlo® Gray Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, reserves the right to change product specifications without notice. Please visit [www.elkay.com](#) for the most current version of product specification sheets. This specification describes product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

1/4" O.D. TUBE
WATER INLET
TO COOLER

3/8" O.D. TUBE CONNECT
COLD WATER SUPPLY

BUILDING WATER
INLET

NOTE: WATER FLOW
DIRECTION

SERVICE STOP
(NOT FURNISHED)

AREAS TO SUPPORT UP TO 300 LBS. STATIC LOAD.

FRONT VIEW

Dimensions:

- Overall width: 28-3/4" (730mm)
- Overall height: 43-5/8" (1108mm)
- Top mounting holes: 9-3/4" (248mm) and 18-3/4" (476mm) from top edge.
- Side mounting holes: 1-1/4" (32mm) from side edge.
- Internal width: 18-3/4" (476mm)
- Internal height: 36-1/2" (927mm)
- Bottom openings: 14-1/4" (362mm) and 8" (203mm) from bottom edge.

Labels:

- SURFACE MOUNTING PLATE
- WASTE TRAP (BY OTHERS)
- SUPPLY (SHUT OFF BY OTHERS)
- OPENINGS FOR (2) OPTIONAL AP99 ACCESS PANELS
- 1/4" (6mm) Ø HOLES FOR MOUNTING PLATE TO WALL
- 5/16"-18 THREADED HOLES FOR MOUNTING FOUNTAINS TO WALL
- 3/8" (10mm) Ø HOLES FOR MOUNTING PLATE TO WALL (20)

SIDE VIEW

Dimensions:

- Overall depth: 21-1/2" (564mm)
- Top mounting holes: 5/8" (16mm) from top edge.
- Side mounting holes: 20-1/8" (511mm) from side edge.
- Bottom openings: 16-1/2" (419mm) from bottom edge.

Labels:

- LOAD BEARING WALL CONSTRUCTION
- ATTACH SURFACE MOUNTING PLATE TO FINISHED WALL
- WASTE 1-1/4" I.P.S. LEFT OR RIGHT SIDE WASTE IS SHOWN IN WALL BUT MAY BE BEHIND WALL.
- INSTALL (2) 1/4" (6mm) SCREWS OR EQUIVALENT (BY OTHERS)
- INSTALL (12) 5/16" (8mm) LAG SCREWS OR EQUIVALENT WITH FLAT WASHERS (BY OTHERS)
- 3/8" I.P.S. SUPPLY (LEFT OR RIGHT)

© 2025 Page 3
EDFPB117FPK spec.pdf