

PRODUCT SPECIFICATIONS

Outdoor Bi-Level Pedestal Fountain with Pet Station Non-Filtered Non-Refrigerated. Features shall include Heavy Duty Vandal Resistant, Pet Fountain, 300 Series Stainless. Furnished with Vandal Resistant bubbler. Mechanical Button activation. Product shall be Floor Mount/Freestanding, for Outdoor applications, serving 2 station(s).

Special Features:	Heavy Duty Vandal Resistant, Pet Fountain, 300 Series Stainless
Finish:	Black (BK), Blue (BLU), Evergreen (EVG), Gray (GRY)
Power:	No Electrical Required
Bubbler Style:	Vandal Resistant
Activation by:	Mechanical Button
Mounting Type:	Floor Mount/Freestanding
Chilling Capacity:	Non-refrigerated
Dimensions (L x W x H):	31" x 26" x 40-5/16"
Approx. Shipping Weight:	170 lbs.
Installation Location**:	Outdoor
No. of Stations Served:	2
**When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.	

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Pet Fountain: Features slow drainage for easy drinking.



Included with Product: Outdoor Fountain Ships in one box.

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

NSF/ANSI 61 (Q_s1) & 372 (lead free)



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

[Installation Instructions \(PDF\) - 1000003946](#)

Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

[Warranty \(PDF\)](#)

PART: _____ QTY: _____

PROJECT: _____

CONTACT: _____

DATE: _____

NOTES: _____

APPROVAL: _____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Trap and service not included.

Technical drawing of a 2PL B.C. (2PL) showing two views. The top view is a plan view of a circular component with a central hole and two side ports. Dimensions include a total diameter of 14 inches (356mm), a central hole diameter of 12 inches (305mm), and a side port diameter of 1/2 inch (13mm). The bottom view is a side view showing the component's profile and a cross-section of the side port.

Technical drawings of three wheelchair accessible urinal configurations, showing dimensions in inches and millimeters.

Left Configuration (Wall-mounted):

- Overall height: 30" (762mm)
- Orifice height: 41-11/16" (1059mm)
- Orifice diameter: Ø 10" (254mm)
- Drain height: 8" (203mm)
- Drain diameter: 1-1/2" (38mm)

Middle Configuration (Pedestal-mounted):

- Overall height: 40-5/16" (1024mm)
- Orifice height: 33-5/16" (846mm)
- Orifice diameter: Ø 10" (254mm)
- Drain height: 27" (737mm)
- Drain diameter: 1-1/2" (38mm)

Right Configuration (Floor-mounted):

- Overall height: 34-11/16" (882mm)
- Orifice height: 33-5/16" (846mm)
- Orifice diameter: Ø 10" (254mm)
- Drain height: 27" (737mm)
- Drain diameter: 1-1/2" (38mm)

* ADA Requirement

A = 3/8" O.D. Unplated copper tube connect
shut off valve by others
B = Access Panel (8" X 10")
C = Removable bottom cover

* ADA Requirement

© 2025 Page 2
LK4420DB spec.pdf