

ELKAY®

PRELIMINARY SPECIFICATIONS

Water Softener Model No.'s ESR3100D-A

PRODUCT SPECIFICATIONS

- Media: Resin
- Product complies with NSF 61 for material safety.
- Product packing and shipment complies with ISTA 1A.

STANDARD FEATURES

- Size: L 312mm x W 526mm x H 591mm
(L 12.3" x W 20.7" x H 23.3")
- A system by-pass valve is included along with the unit.
- Water Inlet/Outlet Pipe: 3/4".
- Drain Pipe: 3/4".

RECOMMENDED USE CONDITIONS

- Water Supply: Standard city tap water.
- Supply Voltage: 110-240 VAC/50-60 Hz
- Plug Type: Type A
- Operating Pressure: 0.15-0.6MPa (22-87 psi)
- Operating Temperature: 5°-38° C (41°-100° F)
- Flow Rate: 1.0 Ton/Hour @ 60 psi

REMOVAL CLAIMS

- Scale causing minerals (Calcium and Magnesium)

IMPORTANT NOTE: Compare the capabilities of this unit with your actual water treatment needs. It is recommended that, before purchasing the unit, to have your water supply tested to determine your actual water treatment needs. Performance will vary depending on local water conditions. Testing was performed under standard laboratory conditions, actual performance may vary.

WARRANTY

Warrantied to be free from defects in material and workmanship for a period of one year from the date of installation or eighteen months from factory shipment, whichever date falls first. Warranty is limited to repair or replacement of defective components.



Job Name: _____

Model: _____ Qty. _____

Contact: _____

Approval Signature: _____

Notes:

In keeping with our policy of continuing product improvement, Elkay reserves the right to change specification without notice. Please visit elkay.com for the most current version.

Printed in U.S.A.
© 2017 Elkay

2222 Camden Court
Oak Brook, IL 60523
630-572-3192
elkay.com

© 2017 Elkay
SPEC00601 (07/2017)